

Accessories






SKU | SE05-C15-DTC41

[Ai SolventVap 2L Rotary Evaporator W/ Chiller & Pump 110V](#)









Ai SolventVap 2L SE05-S2 Rotary Evaporator Standard Package Includes:

SE05-S2 Standard Package





| Part description | Qty | Part image |
|---|------|---|
| Evaporator body with electric flask lift | 1 pc |  |
| Water bath | 1 pc |  |
| Vapor filtering bottle | 1 pc |  |
| Vertical condenser with 2 chilling water ports and 1 vacuum port, glass | 1 pc |  |
| 2L pear shaped evaporating flask, glass (choose based on volume of material to load) | 1 pc |  |

| | | |
|--|-------|---|
| 0.26G/1L round shaped receiving flask, glass | 1 pc |  |
| Glass vapor duct with seal | 1 set |  |
| Glass material feeding tube with valve & PTFE extension hose | 2 pcs |  |
| PTFE vacuum sealing kit | 1 set |  |
| Condenser cap kit | 2 pcs |  |
| Glass shaft cap and evaporator flask quick-release | 2 pcs |  |
| Condenser support and bracket | 1 pc |  |
| Condenser support securing screw | 1 pc |  |
| Receiving flask ball joint clamp | 1 pc |  |
| GL14 connector | 3 pcs |  |
| 3-prong 110V US power cord for evaporator | 1 pc |  |
| Silicone vacuum tubing | 10 ft |  |
| Mechanical vacuum gauge | 1 pc |  |
| Ai plexiglass water bath cover for 2L SolventVap | 1 pc |  |
| Users manual | 2 pcs |  |

C15 Package

| Part description | Quantity | Part image |
|--|----------|---|
| Ai -15°C/5°F 17L/min recirculating chiller | 1 pc |  |
| 3/8" insulated chilling fluid tubing | 11 ft |  |
| Rubber chilling fluid connector | 2 pcs |  |
| Chilling fluid connector gaskets | 2 pcs |  |
| Brush | 1 pc |  |
| Power Cord (110) | 1 pc |  |

DTC-41 Package

| | | |
|---|------|---|
| ULVAC DTC-41 1.6 cfm full chemical-resistant oil-free diaphragm pump | 1 pc |  |
| White premium food grade silicone vacuum hose (3 ft) | 1 pc |  |
| Power Cord with plug (may be hardwired to unit or with a detachable plug) | 1 pc |  |
| Threaded Hose Barb (ID: 6mm OD: 9mm) with O-Ring (CS: 2.5 mm ID: 10 mm) (May be Installed on the unit) | 4 pc |  |